


F902-11TR

Harmony Wall Mount Angled Shower Arm

artos®

OPERATING SPECIFICATIONS



OPERATING PRESSURE

Minimum: 20psi
Maximum: 125psi
Recommended: 30psi-90psi

Above 90psi, it may be necessary to install a pressure reducer.

CONNECTION TYPE

1/2" Male NPT x2

MATERIAL

Solid Brass

INSTALLATION TYPE

Wall Mounted

INSTALLATION DIMENSIONS

Maximum Installation hole diameter: 1-3/8"

REQUIREMENTS

This unit requires a control

STANDARDS

To view all standards, please visit product approvals in our learning hub at artos.us.com

All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

F902-11TR

Harmony Wall Mount Angled Shower Arm

artos®

PRODUCT DIMENSIONS

