

F909BNSVO

3-Way Non-Shared Diverter Valve with Off Position

artos®

OPERATING SPECIFICATIONS



OPERATING TEMPERATURE

Maximum: 176°

OPERATING PRESSURE

Minimum: 20psi

Maximum: 125psi

Recommended: 30psi-95psi

Above 90psi, it may be necessary to install a pressure reducer

FLOW RATE

6.9 USGPM at 60 psi

INLET/OUTLET CONNECTIONS

(3) 1/2" Female NPT Outlets

(1) 3/4" Female NPT Inlet

MATERIAL

Solid Brass

STANDARDS

ASSE 1016.ASME A112.18.1/CSA B123.1 Certified

CUPC Approved

To view all standards, please visit product approvals in our learning hub at artos.us.com

Operates with 1-3 Outlet Functions

All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

F909BNSVO

artos®

3-Way Non-Shared Diverter Valve with Off Position

PRODUCT DIMENSIONS

