

FS328

Opera 8" Widespread Bathroom Faucet With
Arc Spout & Lever Handles

artos®

OPERATING SPECIFICATIONS

OPERATING TEMPERATURE

Maximum: 176°

OPERATING PRESSURE

Minimum: 15psi

Maximum: 75psi

Recommended: 20psi-70psi

Above 90psi it may be necessary to install a pressure reducer

FLOW RATE

1.2 USGPM

INSTALLATION DIMENSIONS

Counter-Top Holes: Faucet: 1" Handles: 1 1/4"

Maximum Surface Thickness: 1-3/4"

FEATURES

Valve Bodies and Umbrella Drain Included

Rotating Spout Design

Quick Connect Hose

STANDARDS

To view all standards, please visit product approvals in our learning hub at artos.us.com



All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

FS328

artos®

Opera 8" Widespread Bathroom Faucet With Arc Spout & Lever Handles

PRODUCT DIMENSIONS

