



Geberit Duofix element for wall-hung WC, 120 cm, with Sigma concealed cistern 8 cm, 4.8 / 3 litres, for wood frame wall



APPLICATION PURPOSES

- For metal and wood frame walls
- For Geberit Duofix system walls
- For installation in part- or room-height prewalls
- For installation in room-height partition walls
- For floor constructions 0–20 cm
- For wall-hung WCs

CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- Frame for wall-hung WCs with connection dimensions as per EN 33 and projection up to 70 cm
- Frame with \varnothing 9 mm drilling holes for fastening in wood frame construction
- Frame fulfils standard requirements in accordance with ASME A112.6.2, ANSI Z124.4
- Alternative fastening point for wall anchors
- Rotating foot plates, suitable for installation in U profiles UW 50 and UW 75
- Foot plates that can be mounted in Geberit Duofix system rail without tools, without additional components
- Galvanised non-slip leg supports protected against corrosion

- Connection bend can be mounted without tools at different depths, adjustable range 80 mm
- Interrupted crossbar enables a front flush depth for the vertical outlet bend
- Waste connector bend, extended, for connection in floor
- Geberit Sigma concealed cistern 8 cm, fully insulated against condensation
- Cistern fulfils standard requirements in accordance with ASME A112.6.2 and ANSI Z124.4
- Flush valve fulfils standard requirements in accordance with CSA B125.3, ASME A112.19.5, IAPMO PS-50, ASME A112.19.2 in connection with ceramic appliance listed
- Fill valve fulfils standard requirements in accordance with ASSE 1002, CSA B125.3
- For front actuation, suitable for single, dual and stop-and-go flushes
- Immediate post flush possible with factory setting
- Tool-free installation and maintenance work on concealed cistern
- Water supply connection on the top left
- Protection box for service opening, can be cut to length, protects against moisture and dirt
- With conduit pipe for feed pipe for Geberit AquaClean shower toilets and for connection cable
- Fastening option for electrical connection

TECHNICAL DATA

Flow pressure	10–1000 kPa
Water temperature max.	25 °C
Flush volume, factory setting	4.8 / 3 l
Product material	Steel
Height-adjustable	Yes

SCOPE OF DELIVERY

- Water supply connection R 1/2", compatible with MasterFix and MeplaFix, with integrated angle stop valve and hand wheel
- Elbow tap connector 90°
- Protection box for service opening
- Connection set for WC, \varnothing 90 mm
- Connection bend 90° made of PE-HD, \varnothing 90 mm
- Adapter socket \varnothing 90 mm / 3"
- Fastening and protection material

ACCESSORIES

- Geberit sound insulation set for wall-hung WC
- Geberit Duofix fastening material for stud clearance 50–57.5 cm
- Geberit Duofix set of wall anchors for single installation, corner construction
- Geberit Duofix set of wall anchor extensions

- Geberit Duofix set of foot fastener on rear wall
- Set of wall anchors for single installation, for Geberit Duofix element for wall-hung WC, with concealed cistern 8 cm

<i>Art. no.</i>	<i>B</i> <i>cm</i>	<i>H</i> <i>cm</i>	<i>T</i> <i>cm</i>
111.597.00.2	50	120	8