



Geberit Duofix element for urinal, 112–130 cm, universal



APPLICATION PURPOSES

- For metal and wood frame walls
- For Geberit Duofix system walls
- For installation in part- or room-height prewalls
- For installation in room-height partition walls
- For floor constructions 0–25 cm
- For the installation of Geberit urinal controls
- For mounting urinals

CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating
- Frame fulfils standard requirements in accordance with ASME A112.6.2
- With pull-out plate for lateral fastening above the element on metal or wood profiles or on Geberit Duofix system studs
- Alternative fastening point for wall anchors
- Rotating foot plates, suitable for installation in U profiles UW 50 and UW 75
- Foot plates that can be mounted in Geberit Duofix system rail without tools, without additional components
- Galvanised non-slip leg supports protected against corrosion
- Element height adjustable to urinal, 112–130 cm
- Concealed housing for Geberit urinal flush controls

- Terminal for electrical connection in concealed housing
- Water supply connection on the right, on the concealed housing
- Connection nipple can be mounted without tools
- Premounted stop valve with throttle
- With built-in conduit pipe to rinse the pipeline
- Protection box for service opening 10.5 x 10.5 cm can be cut to length without tools
- Fastening for inlet \varnothing 32 mm, height-adjustable
- Fastening for connection bend, height-adjustable and sound-absorbing
- Urinal fasteners M8 width- and height-adjustable
- Crossbars with centring marks, adjustable without tools
- Additional fastening possible for urinal with accessories

TECHNICAL DATA

Flow pressure	100–800 kPa
Water test pressure max.	1600 kPa
Test pressure air / inert gas max.	300 kPa
Water temperature max.	30 °C
Flow rate at 100 kPa / 1 bar without flow limiter	0.3 l/s
Flow rate at 100 kPa / 1 bar with flow limiter	0.18 l/s
Product material	Steel

Height-adjustable

Yes

SCOPE OF DELIVERY

- Connection nipple NPT 1/2"
- Protection box with cover
- Connection pipe between inlet \varnothing 32 mm and urinal, with seal to urinal
- Pipe interrupter
- Straight connector made of PVC, \varnothing 50 mm
- Seal \varnothing 57 / 50 mm
- Urinal trap \varnothing 50 mm, with seal on urinal
- Fastening and protection material

ACCESSORIES

- Geberit Duofix fastening material for stud clearance 50–57.5 cm
- Geberit Duofix set of wall anchors for single installation
- Geberit Duofix set of wall anchors for single installation, corner construction
- Geberit Duofix set of wall anchor extensions
- Geberit Duofix set of foot fastener on rear wall

INFO

- The connection pipe (1/2") from the concealed housing to the inlet crossbar via the pipe interrupter must be installed by the plumber

Art. no.	B cm	H cm	T cm
111.625.00.2	50	112-130	7.5