



Geberit Duofix element for bidet, 112 cm, universal



APPLICATION PURPOSES

- For metal and wood frame walls
- For Geberit Duofix system walls
- For installation in part- or room-height prewalls
- For installation in room-height partition walls
- For floor constructions 0–25 cm
- For wall-hung bidets with deck-mounted tap

CHARACTERISTICS

- 2025 range
- Statically self-supporting frame, protected against corrosion with powder coating

- With pull-out plate for lateral fastening above the element on metal or wood profiles or on Geberit Duofix system studs
- Alternative fastening point for wall anchors
- Rotating foot plates, suitable for installation in U profiles UW 50 and UW 75
- Foot plates that can be mounted in Geberit Duofix system rail without tools, without additional components
- Galvanised non-slip leg supports protected against corrosion
- Fastening distance for wall-hung bidet 18 or 23 cm
- Height-adjustable bidet fastening
- Fastening for connection bend, height-adjustable and sound-absorbing
- Tap attachments adjustable in width and height

TECHNICAL DATA

Product material	Steel
Height-adjustable	Yes

SCOPE OF DELIVERY

- Connection bend made of PE-HD, ø 50 mm
- Seal ø 44 / 32 mm
- Fastening material

Art. no.	B cm	H cm	T cm
111.520.00.2	50	112	10
New			

New article available from 01.03.2026