



CLEANET ALVIA PLUS

**Shower toilet premium, rimless,
floorstanding
with remote control,
with seat and cover**
82616.4

TECHNICAL DATA

Order no.	82616.4
Certified to	IPX4
Specifications	Shower toilet, rimless, floorstanding Hygienic flush Remote activated / automatic flush siphonic grade 1 with lateral holes
Water inlet	G 1/2" (male)
Outlet	Siphonic vertical
Working pressure	0.07 to 0.7 MPa (0.7-7 bar)
Working temperature	+5 to +35 °C
Min. installation flow rate	5 l/min
Cleaning functions	Rear shower (soft/intense) and lady shower 5 levels pressure adjustment 5 levels nozzle position adjustment 5 levels temperature adjustment Oscillating and pulsating cleaning mode Shower time setting iOS and android app. connection
Dryer function	5 levels temperature adjustment
WC seat and cover	Duroplast, with antibacterial treatment, with lowering system, with user detection
Seat heating	5 levels temperature adjustment
Comfort	Automatic flushing Toilet preflush Back up flush Manual/automatic deodorizing function Automatic lid and seat opening and closing Night light (toilet/ambience) 5 user levels Emergency buttons

Hygiene	Automatic self cleaning of nozzle UV nozzle disinfection E-water nozzle disinfection UVC cleaning water disinfection
Power supply & consumption	220-240V, 50Hz, plug type A with RCD Rated power consumption 1500W Power saving mode Power cord length 1.6m Power consumption in use max. 1600W
Weight	48,0 kg
Mounting acc. incl.	Remote control Outlet pipe 305 mm, order no. 89688.1 Water connection set for shower toilet for external angle valve Angle valve 1/2", cover for lateral opening and fastening kit
Mounting acc. excl.	Outlet pipe 400 mm, order no. 89688.2
Colours	000 – White

SPECIFICATION TEXT

Shower toilet premium, rimless, floorstanding, with remote control, siphonic, hygienic flush Laufen CLEANET ALVIA PLUS, toilet pan sanitary ceramic

Seat and cover duroplastic with antibacterial treatment, seat with heating type, IPX4, AC 220-240V, 50Hz, plug type A with RCD

Remote activated grade 1

dimensions 410 x 675 x 480 mm, concealed fixation

Special feature: remote control, rear shower and lady shower, with adjustable water pressure, temperature and nozzle position, oscillating and pulsating cleaning mode, integrated self cleaning nozzle, heated seat with adjustable temperature, soft closing lid and seat with auto open function and user detection, integrated deodorizing function, integrated night light and power saving mode, 5 user profiles can be saved, with emergency buttons, iOS and android app. connection

Order no. 82616.4

TECHNICAL DRAWINGS / S 1 : 20

