

## StreamLabs® Control Specifications Sheet

### Pro Install Features

- 24/7 leak protection with automatic, remote, and manual shut-off
- Up to \$2,500 homeowner's insurance deductible reimbursement\*
- 4 year product warranty
- Smart home integration with Google Assistant and Amazon Alexa
- Smart Alerts® learning leak detection
- Home & Away leak detection modes
- Up to 5 locations can be viewed in a single app
- Email, text and push alerts
- Extended alert history
- Detailed historical usage data by hour, day, week, month or year
- Automatic monthly valve check to ensure proper operation
- Drip Detect® : Regularly scheduled pinhole leak tests
- Water pressure, air humidity, temperature sensors and alert settings
- Insurance certification letter available upon requests
- Packaging includes hang tag and magnet with StreamLabs technical support contact information

\*1 year of deductible reimbursement, see website for details

### Specifications

<b>App Compatibility</b>	iOS, compatible with iPhone or iPad, Android, compatible with phone or tablet*
<b>Compatible Fitting Types</b>	Double Union SharkBite, Double Union FNPT, Double Union Sweat (1" only)
<b>Compatible Pipe Types</b>	SharkBite Fittings: PEX; Copper; CPVC; PE-RT** Threaded Connection: Any pipe type Sweat Connection: Copper
<b>Universal Power Supply</b>	Input: 100-240VAC ~50/600Hz, 0.5A; Output: 12 V @ 1 A UL Listed 10' cord included, 25' & 50' extension cable sold separately max distance 100'
<b>Water Temperature</b>	Min. 40°F (4.4°C) / max. 105°F (40°C) for optimal flow accuracy
<b>Operating Pressure</b>	Max. 200 psi (14 bar)
<b>Ambient Temperature</b>	Min. 32° F (0° C) / max. 115° F (46.1° C) for optimal flow accuracy
<b>Operating Environment</b>	Indoor use. May be installed outdoors with a NEMA approved enclosure
<b>Life Expectancy</b>	12 years
<b>IP Rating</b>	IP 54 / 56 rating***
<b>Network</b>	Wi-Fi 802.11b/g/n, 2.4 GHz

\*Contact StreamLabs support for most up-to-date compatible version.

\*\*1-1/4" SharkBite fitting not approved for PE-RT use

\*\*\*IP 54 rated for indoor use, IP 56 rating achievable with outdoor NEMA approved enclosure

### Leak Detection Settings

Settings	User Definable
<b>Home Mode: Slow Leak</b>	Flow above 0.1, 0.25, 0.5, 1.0 GPM That lasts longer than 1, 5, 10, 15, 20, 30, or 60 mins
<b>Home Mode: Major Leak</b>	Flow above 2.0, 3.0, 4.0, 5.0, 10.0, 15.0 GPM That lasts longer than 5s, 30s, 1, 5, 10, 20, or 30 mins
<b>Home Mode: Smart Alerts</b>	Control can learn usage habits and notify of any abnormal usage
<b>Away Mode</b>	Flow above 0.1 GPM That lasts longer than 5s, 15s, 30s, 1, or 5 Minutes
<b>Smart Alert</b>	Control can learn usage habits and notify of any abnormal usage and shut off the water
<b>Drip Detect</b>	Daily, Weekly, or Monthly Test (user configurable)
<b>Pressure Alert</b>	LOW: 10 psi, 20 psi, 30 psi, 40 psi HIGH: 70 psi, 80 psi, 90 psi, 100
<b>Humidity Alert</b>	HIGH: 50%, 60%, 70%, 80%, 90%
<b>Water Temperature Alert</b>	LOW: 50°F, 45°F, 40°F, 35°F HIGH: 90°F, 95°F, 100°F, 115°F
<b>Ambient Temperature Alert</b>	LOW: 50°F, 45°F, 40°F, 35°F

streamlabswater.com | (770) 691-5524 | support@streamlabswater.com

### Listings and Approvals

- NSF/ANSI-61, NSF/ANSI-372, FCC, IC

### Dimensions

- All measurements in mm unless otherwise stated

