



GENERAL SPECIFICATIONS FOR 60420 BATHING POOL

INSTALLED SIZE	72-1/8 x 38 x 23 In. (1832 x 965 x 584mm)
WEIGHT	130 Lbs. (59 Kg.)
WEIGHT w/WATER	605 Lbs. (272 Kg.)
GAL. TO OVERFLOW	57 Gal. (216 L)
WHIRLPOOL MIN. OPERATING VOL.	38 Gal. (144 L)
BATHING WELL AT SUMP	18 x 38 In. (457 x 965mm)
BATHING WELL AT RIM	29 x 61-1/2 In. (736 x 1562mm)
WATER DEPTH TO OVERFLOW	14 In. (356mm)
FLOOR LOADING (PROJECTED AREA)	32 Lbs./Sq.Ft. (154 Kgs./Sq.m)
PTS.	25.6
CUBE (FT ³)	52.5

WHIRLPOOL ELECTRICAL SPECIFICATIONS

WHIRLPOOL PUMP	2.1 HP, 14.4 AMPS, 120V
AIR PUMP	1.0 HP, 6.5 AMP, 120V
WHIRLPOOL ONLY-SYSTEM II WHIRLPOOL PUMP	2.1 HP, 15.6 AMPS, 120V

NOTES:

BATH CAN BE INSTALLED EITHER ABOVE OR BELOW FLOOR LINE AS PIER, ISLAND OR PENINSULA TYPE INSTALLATION. SUMP OF BATH IS SUPPORTED BY INTEGRAL FEET. NO ADDITIONAL SUPPORT REQUIRED. ENCLOSING MATERIALS BY OTHERS.

● IF INSTALLING A DECK-MOUNTED FITTING, BEFORE DRILLING ANY HOLES: CHECK FOR INTERFERENCE WITH CIRCULATING SYSTEM PIPING AND DRAIN OVERFLOW. MOUNTING HOLES DRILLED BY INSTALLER.

■ REFER TO INSTALLATION INSTRUCTIONS SUPPLIED WITH WHIRLPOOL FOR ADDITIONAL INFORMATION. FITTINGS NOT INCLUDED AND MUST BE ORDERED SEPARATELY. PROVIDE SUITABLE REINFORCEMENT FOR ALL SUPPORTS.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard Z124.1. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.