



GENERAL SPECIFICATIONS FOR 60080 WHIRLPOOL

INSTALLED SIZE	69-1/2" x 34"-3/4 x 24" (1765 x 883 x 610mm)
WEIGHT	107 Lbs. (49 Kg)
WEIGHT W/WATER	657 Lbs. (298 Kg)
GALLONS TO OVERFLOW	66 Gal. (250 L)
WHIRLPOOL MINIMUM OPERATING VOLUME	49 Gal. (185L)
BATHING WELL AT SUMP	44" x 21" (1118 x 533mm)
BATHING WELL AT RIM	60" x 25-1/2" (1524 x 648mm)
WATER DEPTH TO OVERFLOW	17" (432 mm)
FLOOR LOADING (PROJ. AREA)	38.9 Lbs./Sq. Ft. (190 Kgs/Sq. m)
POINTS	47.6
CARTON VOLUME	63 Cu. Ft. (1.78 Cu. m)
CARTON SHIPPING WEIGHT	160 Lbs. (73 Kg)

WHIRLPOOL ELECTRICAL SPECIFICATIONS

SYSTEM II PUMP	2.0 HP, 15.6 AMPS, 120V
SYSTEM II IN-LINE HEATER	12 AMPS, 120V

NOTES:

BATH CAN BE INSTALLED EITHER ABOVE OR BELOW FLOOR LINE AS PIER, ISLAND OR PENINSULA TYPE INSTALLATION. SUMP OF BATH IS SUPPORTED BY INTEGRAL FEET. NO ADDITIONAL SUPPORT REQUIRED. ENCLOSING MATERIALS BY OTHERS.

● IF INSTALLING A DECK-MOUNTED FITTING, BEFORE DRILLING ANY HOLES: CHECK FOR INTERFERENCE WITH CIRCULATING SYSTEM PIPING AND DRAIN OVERFLOW. MOUNTING HOLES DRILLED BY INSTALLER.

■ REFER TO INSTALLATION INSTRUCTIONS SUPPLIED WITH WHIRLPOOL FOR ADDITIONAL INFORMATION. FITTINGS NOT INCLUDED AND MUST BE ORDERED SEPARATELY. PROVIDE SUITABLE REINFORCEMENT FOR ALL SUPPORTS.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard Z124.1. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided leaflet.