



Wall Mounted Toilet	Dimension	Weight	Order number
Flush water quantity: 1.2/0.8 gal, Washdown model, Flushing rim: Rimless, Concealed fixation, Includes connecting set for SensoWash, cUPC listed: Yes			
Colors			
00 White 20 HygieneGlaze (an antibacterial ceramic glaze that provides almost indefinite effectiveness)			
Variant			
White High Gloss, Flush water quantity: 1.28/0.8 gal, Flush system: washdown model, Outlet horizontal, WaterSense: Yes, ADA: Yes		57.320 lb	252959..92
White High Gloss, HygieneGlaze, Flush water quantity: 1.28/0.8 gal, Flush system: washdown model, Outlet horizontal, WaterSense: Yes, ADA: Yes		57.320 lb	252959..92
Spare parts			
Installation Set	5 3/8 x 4 1/8 "	0.948 lb	005072
Actuator Plate A1 Plastic, Dual Flush, Trip lever type: Mechanical, Flush operation technology: Manual, Installation Type: surface mounted, Includes mounting frame, including mounting kit, Includes push rod	8 1/2 x 3/8 "	0.69 lb	WD5008
Connection Set	8 5/8 x 10 1/4 "	1.543 lb	100691
Suitable products			
Shower toilet seat Matches series ME by Starck, Starck 2, Starck 3, DuraStyle, Bento Starck Box, White, Slow close, Seat material type: Duroplast, Lid material type: Duroplast, Water position adjustment: 5 Steps, Number of spray intensity options: 3 Steps, Number of spray temperature options: 4 Steps, Water position adjustment: 5 Steps, Rearwash, Frontwash, Pulsing shower spray: Oscillating, Remote control, Controller, Self-cleaning function, Decalcification function, Holiday mode, Night light, cUPC listed: No, UL: No, 14 5/8 x 21 1/4 "	14 5/8 x 21 1/4 "		611000

ME by Starck Wall Mounted Toilet # 252959..92 / 252959..92

|< 14 5/8 " >|

<p>In-Wall Tank & Carrier Standard Includes HDPE toilet wall-mounted outlet bend DN 90/90, Powder-coated, Installation Type: In lightweight stand construction, Installation Type: Drywall, Max. projection toilet: 24 5/8 ", Adjustable height: 9 1/2 ", Trip lever type: Mechanical, Trip lever placement: Front, Adjustable flush volumes, Flush type: Dual Flush, Insulated tank, Self-supporting, Suitable for panelling with plasterboards, 23 1/4 x 3 1/2 "</p>	<p>WD1022</p>
<p>Shower toilet seat Matches series ME by Starck, Starck 2, Starck 3, Darling New, Bento Starck Box, Slow close, Water position adjustment: 5 Steps, Number of spray intensity options: 3 Steps, Number of spray temperature options: 4 Steps, Water position adjustment: 5 Steps, Rearwash, Frontwash, Pulsing shower spray: Oscillating, Number of user profiles: 4, Self-cleaning function, Decalcification function, Energy saving mode: Adjustable, Night light, 14 3/8 x 20 1/2 "</p>	<p>613000</p>

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.