

# F502-10

Opera Round 5-Hole Deck Mounted Tub Filler  
with Hand Shower

artos®

## OPERATING SPECIFICATIONS



### OPERATING TEMPERATURE

Maximum: 176°

### OPERATING PRESSURE

Minimum: 15psi

Maximum: 75psi

Recommended: 25psi-70psi

Operating pressures (on hot and cold lines) should be kept as balanced as possible, in order to assure the maximum efficiency

### FLOW RATE

Tub Filler: 6.0 USGPM

Hand Shower: 2.0 USGPM

### MATERIAL

Solid Brass

### FEATURES

Pull-Out Hand Shower with 25" Hose

Rotating Spout Design

### STANDARDS

Faucet handles are ADA-compliant and require  $\leq 5$  pounds of operating force.

For a complete list of applicable standards, please visit the Product Approvals section of our Learning Hub at [artos.us.com](http://artos.us.com).



WESTOVER, INC

4011 S 60TH ST, OMAHA, NE 68117

[WWW.ARTOS.US.COM](http://WWW.ARTOS.US.COM)

T: 402-397-3344

All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

# F502-10

Opera Round 5-Hole Deck Mounted Tub Filler  
with Hand Shower

## PRODUCT DIMENSIONS

