

FS510TK

Round Floor Mount Tub Filler Trim Kit with Hand Held Shower

artos®

OPERATING SPECIFICATIONS



OPERATING PRESSURE

Minimum: 15psi

Maximum: 75psi

Recommended: 20psi-70psi

Above 90psi it may be necessary to install a pressure reducer

Operating pressures (on hot and cold lines) should be kept as balanced as possible, in order to assure the maximum efficiency.

OPERATING TEMPERATURE

Maximum: 176°

FLOW RATE

Tub Filler: 6.0 USPGM

Hand Shower: 2.0 USGPM

REQUIREMENTS

FS500V Floor Mount Tub Filler Valve

FEATURES

Rotating spout

Integrated Shower Wand

150cm Wand Reach

Easy Clean Jet Nozzles

STANDARDS



All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

FS510TK

Round Floor Mount Tub Filler Trim Kit with Hand Held Shower

artos®

PRODUCT DIMENSIONS

