

F902-26

Round Multifunction Shower Head

artos®

OPERATING SPECIFICATIONS

OPERATING PRESSURE

Minimum: 15psi
Maximum: 75psi
Recommended: 20psi-70psi

Above 90psi it may be necessary to install a pressure reducer.



FLOW RATE

1.8 USGPM

CONNECTION TYPE

1/2" Female NPT

MATERIAL

ABS Plastic and Silicon

REQUIREMENTS

This unit requires a Control and Shower Arm

FEATURES

Easy clean anti-scale silicon nozzles

STANDARDS

To view all standards please visit product approvals in our learning hub at artos.us.com



All technical specifications, product details, and pricing are subject to change without prior notice. Artos makes every effort to ensure accuracy; however, errors or omissions may occur. It is the responsibility of the installer, designer, or purchaser to verify all critical dimensions, installation requirements, and compliance with applicable codes prior to use.

Artos assumes no liability for damages, losses, or injuries resulting from the use of this documentation or from product installation, operation, or maintenance performed outside of Artos instructions and applicable codes. Product warranties are limited to those expressly stated by Artos. Please refer to official warranty documentation for complete terms and conditions.

All drawings, manuals, and specifications are the property of Artos and may not be reproduced, distributed, or altered without prior written permission.

F902-26

Round Multifunction Shower Head

artos®

PRODUCT DIMENSIONS

