

# ESSENCIA DESIGN

72" x 36" x 24" (FREESTANDING)

Essencia evokes essence—the elemental aspects of the inner being.



Essencia Design 7236 with Illuzio Chromatherapy

## PRODUCT NO.

MODEL	TMU	TUB
Freestanding	BESSOFN0T-XX	BESSOFN0N-XX

THERMOMASSEUR (TMU)	
Hydro-thermo massage • Air jet system	\$
Jets	46
1 heated backrest	Included
MiaPlus® Control* (not installed)	Included
BU-Touch Control Application	Included
Geysair®	Included
AromaCloud®	N/A
Illuzio Chromatherapy <a href="#">BCHRO6</a>	\$

TUB Soaker	
AromaCloud®	N/A
Illuzio Chromatherapy <a href="#">BCHRO6</a>	\$
WarmTouchShell® <a href="#">BWTS</a>	\$
DOT control	Included with therapy

## FEATURES

Installation type	Freestanding		
No. of bathers	↓	Imp. gallons	46
US gallons	55		

## INTEGRATED WASTE & OVERFLOW [BOVERINI-XX](#)

White <a href="#">01</a> , Chrome <a href="#">07</a> , Brushed Nickel <a href="#">09</a> , Polished Nickel <a href="#">10</a> , Matte White with UltraVelour finish <a href="#">32</a>	Installed & Included
--	----------------------

## STANDARD COLOR

 White <a href="#">01</a>	Included
--	----------

## OPTIONS (UPCHARGE APPLICABLE)

### COLOR

 Black / White <a href="#">66</a>	\$
--	----

### FINISH

UltraVelour Matte Finish (white only) <a href="#">BVEL2</a>	\$
---	----

### INTEGRATED WASTE & OVERFLOW [BOVERINI-XX](#)

Matte Black <a href="#">19</a> , Satin Brass <a href="#">18</a>	\$
---	----

### ISLAND TUB DRAIN™\*\*

Island Tub Drain™ <a href="#">BISLDD</a>	\$
Cast Iron Island Tub Drain™ <a href="#">BISLDDCI</a>	\$

### IF REQUIRED BY CONSTRUCTION CODE

Brass waste & overflow kit <a href="#">BDRCOB</a>	\$
Brass waste kit <a href="#">BDRCB</a>	\$



Don't forget to specify the **finish of the integrated waste & overflow.**

\* For TMU, control must be wall-mounted. Faucets must be freestanding or wall-mounted.

\*\* An Island Tub Drain™ is required when there is **no access under the bath.**

TOTAL PRICE	\$
-------------	----

## FOR THE INSTALLER

SCAN TO VIEW INSTALLATION VIDEO (3:20 MIN)






## ESSENCIA DESIGN (FREESTANDING)



### INSTALLATION



LETTER	DESCRIPTION	MEASURE
A	Total length	72"
B	Total width	36"
C	Bathing well length (at jets height)	44 7/8"
D	Bathing well width (at jets height)	22 5/8"
E	Deck width (top)	1 5/8"
F	Deck width (backrest round edge)	3 1/2"
G	Deck width (side round edge)	3 1/8"
H	Center drain to center air intake (long axis)	3 1/2"
I	Center drain to center air intake (trans axis)	3 1/2"
J	Center drain to deck edge	30 1/2"
K	Bath height	24"
L	Height from drain to top of deck	19 1/4"
M	Height from drain to center of overflow	16 5/8"
N	Slope	40°
O	Slope of backrest	29°
P	Base length	32 3/8"
Q	Base width	19"

- Indicates heated backrest (TMU)
- ☄ Indicates WarmTouchShell® position (TUB)

### TECHNICAL SPECIFICATIONS

<b>Hot water supply required</b>	The hot water supply should be 70% or more of the bath's total water capacity.
<b>Turbine</b>	Access to the pump must be at least 18" x 22". <b>Standard connection is 20 A, 120 V, 60 hz</b> , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). <b>For any additional option, a second line is needed 15 A, 120 V, 60 hz</b> , dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
<b>Others</b>	<ul style="list-style-type: none"> <li>- The Geysair is located on the same side as the heated backrest. It must <b>NOT</b> be relocated. It must be <b>connected to the hot water supply</b> and be accessible (provide access).</li> <li>- Faucet must be freestanding or wall-mounted.</li> <li>- The turbine must be <b>remotely installed</b>.</li> <li>- TMU: Control must be wall-mounted.</li> </ul>

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations ([www.bainultra.com/documentation/documentation](http://www.bainultra.com/documentation/documentation)).

<b>Cutting template</b>	# 90000071
<b>Approx. shipping weight</b>	305 lbs
<b>Turbine power</b>	550 W
<b>Air heater</b>	600 W
<b>WARRANTY</b>	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

\* Some restrictions apply | [www.bainultra.com/warranty](http://www.bainultra.com/warranty)

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.