



5436MT



When ordering, please specify tile flange locations.

54" x 36" x 3" (exterior bottom of base)	
MULTIPLE, LOW-PROFILE THRESHOLD smooth floor	
Center Drain	
Acrylic CXL®	DoloMatte®
135 lbs / 61 kg	152 lbs / 69 kg



Model #	Material	Color / Finish	
SB5436MT	Acrylic CXL®	White (CWH) or Biscuit (CBS) / Gloss	
SBDM5436MT	DoloMatte®	White (CWH) / Matte	

Must specify color code on order. DoloMatte available in white only. Not for use in steam shower applications.

Options <i>Must be ordered at time of purchase</i>
Quick Ship (QSPRI) Reduces lead time. Please call for availability.
Radiance® (RAD100) Shower floor heating system. Radiance heating grids are fully integrated within the acrylic shell structure of the shower floor. Requires a 110-volt, 15 amp GFCI and remote installation of control box & keypad.
Pre-Leveled Foam Base (PLFSB)
PVC Drain Kit Finishes Chrome included with shower base Brushed Nickel upcharge (SBSQDBN)

Accessories
Drain Kit Solid Brass Drain Kit with Stainless Steel Trim (SBSQDSB)
Teak Shower Seat Premium Natural Stainless (TK-SSEAT2416BNS) High-Polished Stainless (TK-SSEAT2416BHP) Standard Natural Stainless (TK-SSEAT2215NS) High-Polished Stainless (TK-SSEAT2215HP)
Teak Bath Mat (TKMAT3018) Measures 30" x 17.5" x 1" Custom sizes also available. Contact MTI for details.
Teak Shower Tray (TK5436MT) Contact MTI for pricing



Factory-installed tile flange is 1/16" thick.
Account for this thickness when planning final opening size.

IMPORTANT ORDERING & INSTALLATION INFORMATION

- Factory-installed tile flange on 1, 2 or 3 sides to facilitate installation. Must specify tile flange location(s) on order.
- 3.5" drain opening pre-drilled.
- Dimensions provided represent the length and width of the bottom of the base without tile flange. See Installation Instructions.
- Add proper wet-bedding compound to fully support bottom of shower base. Optional factory installed Pre-Leveled Foam Base negates the need to wet bed when installing on a flat, level subfloor. See installation instructions.
- All bases are in accordance with CSA B45.5/IAPMO Z124 standard and compliant with ASTM C 1028-07 coefficient of friction. DoloMatte bases meet ANSI A137.1/A326.3 coefficient of friction and AS HB198:2014 pendulum slip resistance testing.

- Options and accessories may be packaged inside the box. Always check packaging before discarding.
- All product measurements are ±1/2".
- Specifications and configurations are subject to change without notice.
- Measurements herein supersede all others published prior to publication date below.

See the Installation & Operation Manual for more details.

MTI's Customer Service: Monday-Friday 8am-6pm EST

800-783-8827 or service@mtibaths.com

CSA # MTSB-5436MT

HURL # MTSB-DM5436MT

©2026 by MTI Baths, Inc. Modification Rights Reserved

mti
BATHS

Rev. 06 08 2026