
KWC ZOE touch light PRO





A 215, flexible connection hoses, mains receiver



KWC-No.

10.201.242.127FL

Finish

decor steel

Kitchen with LUMINAQUA® LED-technology, touch light PRO

Electronic controlled

- touch light PRO technology
- touch'n'flow 1-2-3
- 3 preset temperatures and flow rates
- Position of control unit only possible on the right side
- gap between wall and centre of mounting hole min. 42 mm
- Microprocessor-control
- touch'n'flow 1: cold water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 2: warm water, 50% flow rate can be individually adjusted and saved
- touch'n'flow 3: hot water, 50% flow rate can be individually adjusted and saved
- with cleaning programme
- duration of water flow safety indication: switch off automatically after 10 minutes
- temperature limit can be adjusted
- hot water disinfection (5 minutes) can be adjusted
- can be restored to factory settings
- Covered pull-out spray
- ergonomic spout alignment, shape and handling
- KWC JETCLEAN technology
- Neoperl® Cascade®
- automatic diverter reset
- integrated ON/OFF push-button with automatic shut-off after 30 minutes
- up to 500 mm pull-out length
- hose surface to fit faucet surface
- Hose guide, swivelling 270°
- touch light PRO control unit, maintenance-free
 up-to-date microprocessor and drive technology
- tried-and-tested valve technology
- incl. installation materials
- designed for wired connection to 1 operating unit (standard)
- Flexible connection hoses 3/8"
- Fastening by means of threaded sleeve M33 x 1.5
- Mounting hole size ø35 mm

Flow rate normal spray 9 l/min (3 bar) Flow rate needle spray 10 l/min (3 bar) Acoustic group I Subject to technical, range and model changes. Dimensions in mm. Scope of delivery:

- Mains receiver 100-240 V / operating voltage 15 V / cable length 900 mm
- To be ordered separately (optional or if necessary):
- Extension set 1500 mm 2.536.352, comprising: stainless steel hose 1500 mm, ¾" x ¾", double nipple, sealing material